



FOR	LEVEL SWITCH		
MOUNTING	TOP		
ENCLOSURE	WEATHER PROOF		
MAX. PRESSURE	10	kgf/cm ²	
MAX. TEMP	120	°C	
CABLE ENTRY	PF 1/2"(F)		
	<input type="checkbox"/>		

NO.	DESCRIPTION	MATERIAL	REMARK
1	HEAD	AL.C	
2	PROCESS CONN.	<input type="checkbox"/> 304 SS <input type="checkbox"/> 316L SS	
3	FLOAT	316L SS	
4	MAGNET	ALNICO	
5	FIXED BAR	316L SS	
6	STOPPER	316L SS	
7	PIN	316L SS	
8	WEIGHT	316L SS	
9	STOPPER	316L SS	
10	GUIDE PIPE	316L SS	

SWITCH	TYPE & FROM	MICRO, 1/SPDT
	RATING	AC 250V 15A DC 125V 0.5A

PROCESS CONN. SIZE	
<input type="checkbox"/>	125A JIS 10K RF(MIN.)
<input type="checkbox"/>	

TAG NO.	Q'TY	L1

NOTE
1. GENERAL TOLERANCE ±3mm EXCEPT AS NOTED.

	.	.				HITROL CO., LTD. TITLE LEVEL SWITCH HM-12W	SCALE	UNIT	SHEET NO.
	.	.					N.S	mm	/
	.	.					PROJECT		
	.	.					DRAWING NO. HM12W-A-01		
	NOV. 2017	1ST ISSUE	D Y KIM	B S SUNG	Y H KIM				
NO.	DATE	REVISION	REV'D BY	CHK'D BY	APP'D BY				

This drawing is the property of HITROL and shall not be copied, communicated, or given for third-party permission except with our written permission