



SPECIFICATION	
POWER SOURCE	<input type="checkbox"/> AC 85~264V, 50/60Hz <input type="checkbox"/> DC 24V
INSTALLATION	PLUG-IN
DISPLAY	4 DIGIT(RED)/0.4inch
INPUT	mA, 2-wire, V
OUTPUT	<input type="checkbox"/> DC 4~20mA, 2-Alarm, 1-Control <input type="checkbox"/> DC 4~20mA, 2-Alarm, 1-Control, RS485
WEIGHT	APPROX. 350g
AMBIENT TEMP.	OPER. -10~60°C
AMBIENT HUMIDITY	10~90%
HOUSING MATERIAL	ABS Plastic(White)

△	.	.			
△	.	.			
△	.	.			
△	.	.			
△	MAY. 2018	1st ISSUE	D Y KIM	B S SUNG	Y H KIM
NO.	DATE	REVISION	REV'D BY	CHK'D BY	APP'D BY

HITROL HITROL CO., LTD.
TITLE
**ALARM SETTER
HTA-4003**

SCALE N.S	UNIT mm	SHEET NO. /
PROJECT		
DRAWING NO. HTA4003-A-01		

This drawing is the property of HITROL and shall not be copied, communicated, or given for third-party except with our written permission