


FOR	FLOW SWITCH	
MOUNTING	FLANGE	
ENCLOSURE	WEATHER-PROOF	
MAX. PRESSURE	10	kgf/cm ²
MAX. TEMP	80	°C

CABLE ENTRY	PF 3/4"(F)
	<input type="checkbox"/>

NO.	DESCRIPTION	MATERIAL	REMARK
1	HOUSING	AL.C	
2	PROCESS CONN.	<input type="checkbox"/> 304 SS <input type="checkbox"/> 316L SS	
3	SHAFT	316L SS	
4	PADDLE	316L SS	0.2t

PROCESS CONN. SIZE	
<input type="checkbox"/>	80A JIS 10K RF
<input type="checkbox"/>	

SWITCH	
TYPE	MICRO
RATING	AC 250V 10A / DC 125V 0.5A
FORM	1-SPDT



TAG. NO.	Q'TY	NOZZLE LENGTH
		70(STD.)

NOTE
1. GENERAL TOLERANCE $\pm 3\text{mm}$ EXCEPT AS NOTED.

						HITROL CO., LTD.	SCALE N.S	UNIT mm	SHEET NO. /
							TITLE PADDLE TYPE FLOW SWITCH HFS-12S	PROJECT	DRAWING NO. HFS12S-A-01
	MAY. 2018	1ST ISSUE	D Y KIM	B S SUNG	Y H KIM				
NO.	DATE	REVISION	REV'D BY	CHK'D BY	APP'D BY				

This drawing is the property of HITROL and shall not be copied, communicated, or given for third-party except with our written permission.