



SPECIFICATION

POWER SOURCE	AC 24V or DC 24V
POWER CONSUMPTION	approx. 2VA
OUTPUT	potential free change over contact SPDT
RESPONSE TIME	approx. 0.2m sec
CONTACT RATING	AC 250V, 5A max.
ALARM TEMP.	-20 ~ +60°C
INPUT SIGNAL	PANEL REAR (RAIL SYSTEM)

ELECTRODE DATE

SWITCHING	operating resistance
SENSITIVITY	0 ~ 30KΩ
MEASURING CIRCUIT	Noram sensitivity DC 24V
CURRENT AND VOLTAGE	max. 10mA DC

NOTE

1. GENERAL TOLERANCE IS $\pm 3\text{mm}$ EXCEPT AS NOTED.

	.	.						HITROL CO., LTD.	SCALE	N.S	UNIT	mm	SHEET NO.	/
	.	.							PROJECT					
	.	.							DRAWING NO.					
	.	.												
	MAY. 2018	1ST ISSUE	D Y KIM	B S SUNG	Y H KIM									
NO.	DATE	REVISION	REV'D BY	CHK'D BY	APP'D BY									

TITLE
CONTROL UNIT
HLC-200F

HLC200F-A-01

A4(210mm x 297mm)

This drawing is the property of HITROL and shall not be copied, communicated, or given for tiers except with our written permission.