



SPECIFICATION

POWER SOURCE : <input type="checkbox"/> AC 110/220V ±10%, 50/60Hz <input type="checkbox"/> DC 24V
POWER CONSUMPTION : approx. 3VA
OUTPUT : Potential free change over contact
RESPONSE TIME : approx 0.2m sec
CONTACT RATING : AC 250V, 5A max.
AMBIENT TEMP. : -20 ~ +60°C

ELECTRODE DATA

SWITCHING : Operating resistance 0~5KΩ	
SENSITIVITY (NORMAL) : Return resistance 20KΩ over	
MEASURING CIRCUIT	Normal sensitivity AC 6V
CURRENT & VOLTAGE	High sensitivity AC 12V

* P : PUMPING, D : DRAIN

						HITROL CO., LTD. TITLE CONTROL & ALARM UNIT HLC-300	SCALE N.S	UNIT mm	SHEET NO. /	
							PROJECT			
							DRAWING NO.	HLC300-A-01		
	MAY. 2018	1ST ISSUE	D Y KIM	B S SUNG	Y H KIM					
	NO.	DATE	REVISION	REV'D BY	CHK'D BY		APP'D BY			

This drawing is the property of HITROL and shall not be copied, communicated, or given for tiers except with our written permission.