



FOR	ELECTRODE TYPE LEVEL SENSOR
MOUNTING	TOP FLANGE
ENCLOSURE	WEATHER PROOF (IP65)
MAX. PRESSURE	10 kgf/cm <sup>2</sup>
MAX. TEMP	80 °C

CABLE ENTRY	PF 3/4"(F)
	<input type="checkbox"/>

COMBINATION UNIT	
CONTROL UNIT	<input type="checkbox"/> HLC-200
	<input type="checkbox"/> HLC-300

NO.	DESCRIPTION	MATERIAL	REMARK
1	HOUSING	AL.C	
2	PROCESS CONN.	304 SS	
3	ELECTRODE	316L SS	ø6
4	INSULATION	<input type="checkbox"/> TEFLON <input type="checkbox"/> P.P	
5	GROUND ELECTRODE	316L SS+P.P	ø5

PROCESS CONN. SIZE	<input type="checkbox"/> PT 2" SCREW
	<input type="checkbox"/>

TAG. NO.	Q'TY	L1	L2	L3	L4	L

**NOTE**  
1. GENERAL TOLERANCE : ±5mm EXCEPT AS NOTED.

△					
△					
△					
△					
△	Apr. 2018	1ST ISSUE	D Y KIM	B S SUNG	Y H KIM
NO.	DATE	REVISION	REV'D BY	CHK'D BY	APP'D BY

**HITROL** HITROL CO., LTD.  
TITLE  
**ELECTRODE TYPE LEVEL SENSOR  
HE-5H**

SCALE N.S UNIT mm SHEET NO. /  
PROJECT  
DRAWING NO. HE5H-A-01

This drawing is the property of HITROL and shall not be copied, communicated, or given for third-party permission without our written permission.