


FOR	FLOAT TYPE LEVEL SWITCH	
MOUNTING	TOP	
ENCLOSURE	WEATHER PROOF (IP65)	
AMBIENT TEMP.	-20 ~ +60 °C	
MAX. PRESS.	ATM	kgf/cm <sup>2</sup>
MAX. TEMP.	60	°C

CABLE ENTRY	PF 3/4"(F)
	<input type="checkbox"/>

NO.	DESCRIPTION	MATERIAL	REMARK
1	HOUSING	PC	
2	PROCESS CONN.	PVC	
3	PROTECTION PIPE	PVC	
4	FLOAT	PP	

PROCESS CONN. SIZE	
<input type="checkbox"/>	PT 1-1/2"(M) SCREW
<input type="checkbox"/>	

SWITCH	
TYPE	REED
RATING	DC 24V, 0.5A
FORM	1-SPST



LENGTH (mm)		SWITCH ACTION	
L1		<input type="checkbox"/> ↑	<input type="checkbox"/> ↓
L		<input type="checkbox"/> ON	<input type="checkbox"/> OFF

NOTE  
 1. GENERAL TOLERANCE ±3mm EXCEPT AS NOTED.  
 2. ACCURACY : ±5mm  
 3. Q'TY : \_\_\_ SET(S)  
 4. TAG NO. : \_\_\_\_\_

	.	.				HITROL CO., LTD. TITLE FLOAT TYPE LEVEL SWITCH HR-10T-1F	SCALE	UNIT	SHEET NO.
	.	.					N.S	mm	/
	.	.					PROJECT		
	.	.					DRAWING NO.		
	OCT. 2017	1st ISSUE	D Y KIM	B S SUNG	Y H KIM		HR10T-A-01		
NO.	DATE	REVISION	REV'D BY	CHK'D BY	APP'D BY				

This drawing is the property of HITROL and shall not be copied, communicated, or given for third-party except with our written permission.